


道路灯系列


引领照明方向 提升城市照明品位



结构尺寸



配光曲线



RM LD - 024



RM LD - 025

- 型号: RM-1001
- 防护等级: IP65
- 配用光源: 高压钠灯110W-400W/金属卤化灯150W-400W/无极灯85W-165W
- 额定电压和频率: 220V (± 10%) 50Hz
- 安装管径: 60mm
- 防触电保护等级: I类
- 灯体为压铸铝, 经防腐处理后, 表面聚脂粉体涂装
- 灯体内置高纯铝反光器, 耐高温光学玻璃灯罩
- 紧固件螺钉、螺母为不锈钢
- 适用高度/臂长: 6m-12m/1m-2.8m
- 灯杆为钢件, 经热镀锌处理后, 表面静电粉末喷涂
- Model No.: RM-1001
- Protection class: Ip65
- Lighting source: high-pressure sodium lamp 110W-400W, metalhalogen lamp 150W-400W, non-polar lamp 85W-165W
- Rated voltage and frequency: 220V (± 10%) 50Hz
- Tube diameter for installation: 60mm
- Protection class against electric shock: I
- The body of lamp is made of die-cast aluminum, and is coated with polyester powder after corrosion-resistance treatment.
- Repercussion device of high-purity aluminum and heat-resistant glass lampshade
- Screws and nuts made of stainless steel
- Applicable length/ arm length: 6m-12m/ 1m-2.8m
- The column is made of steel, after treatment, the surface by galvanizing electrostatic powder spraying

道路灯系列

引领照明方向 提升城市照明品位



RMLD - 026



RMLD - 027



RMLD - 028



RMLD - 029